

MIL/MC3008 Military Battery Charger



- 5 way charger for TNC-2188 military batteries. Also available as 2, 3 or 4 output.
- 115/230V ac or 24V dc powered for vehicle use.
- Robust construction and easy grip handles for portability
- Vehicle mounting kit includes mounting plate and dc power lead

Charger functions include:

- Pre charge test – to check battery fit to charge
- Normal charge – 14 hour timed charge
- Balance charge – trickle charge to maintain capacity at completion of normal charge.

The MIL/MC3008 is designed for charging most types of military battery, please specify battery type when ordering. The unit is designed and manufactured in the UK giving the user unbeatable product support.

Dimensions	290mm x 190mm x 160mm
Weight	6kg
Normal charge current	440mA
Balance charge current	220mA
Charge termination	Timed
Number of channels	5
Output	Flying lead
Output power	60 Watts
Supply voltage	110V/230V ac internally switched 50/60Hz, 20V-33V dc
Charging temperature	0°C to +55°C
Storage temperature	-20°C to +70°C

MIL Power Limited.
Celtic House, 44 Ball Moor,
Buckingham. MK18 1RQ
England

MIL Power

Tel No. +44 (0) 1280 812402
Fax No. +44 (0) 1280 814169

Email sales@milpower.co.uk
Web Page. www.milpower.co.uk