

MIL/MC3105 Military Battery Charger for MIL/R4516



- 2 way charger for NiCD or NiMH MIL/R4516 batteries. Also available as 5 output.
- 115/230V ac, or 24V dc supply for vehicle use
- Robust construction and easy grip handles for portability
- Vehicle mounting kit includes mounting plate and dc power lead

Charger functions include:

- Pre charge test – to check battery fit to charge
- Fast charge – with voltage profile charge termination
- Balance charge – trickle charge to maintain capacity at completion of normal charge.

The MIL/MC3105 is designed and manufactured in the UK giving the user unbeatable product support.

Dimensions	290mm x 190mm x 160mm
Weight	5kg
Fast charge current	600mA
Balance charge current	50mA
Charge termination	Voltage profile with timed back up
Number of channels	2
Output	Flying lead
Output power	15 Watts
Supply voltage	110V/230V ac internally switched 50/60Hz, 20V-30V dc
Charging temperature	0°C to +50°C
Storage temperature	-20°C to +70°C

MIL Power Limited.
Celtic House, 44 Ball Moor,
Buckingham. MK18 1RQ
England

Tel No. +44 (0) 1280 812402
Fax No. +44 (0) 1280 814169

MIL Power

Email sales@milpower.co.uk
Web Page. www.milpower.co.uk