

## MIL/BA-5567/U Battery



- High performance Lithium Sulphur Dioxide non-rechargeable battery.
- High reliability due to all welded construction
- Unit contains safety vented cell

This battery is engineered and designed for use in a world wide tactical environment, and is manufactured to meet and exceed US MIL-SPEC and ISO9000 methods and procedures. This battery meets the requirements of MIL-B-49430 (Li-SO<sub>2</sub>) with reference to MIL-STD-810 for:

Battery voltage  
Mechanical and thermal shock

Capacity test  
Vibration

Electrolyte leakage  
Insulation resistance

For use in	PVS-4, PVS-5B, PVS-5C, PVS-7A, PVS-7B, TVS-5
Replacement for	BA-5567/U, BA-1567/U, BA-5367/U
Cell chemistry	Lithium Sulphur Dioxide
Nominal voltage	3.0 Volts
Typical capacity	0.86Ah
Minimum service life	18 hours @ 50mA discharge at 25°C to 2.0V
Nominal dimensions	26 x 19mm
Maximum weight	20 gms
Case material	High impact engineering plastic
Operating temperature	-29°C to +55°C
Disposal	Check with local regulations for proper disposal

**MIL Power Limited.**  
**Celtic House,**  
**44 Ball Moor,**  
**Buckingham. MK18 1RQ**  
**England**

**MIL Power**

Tel No. +44 (0) 1280 812402  
Fax No. +44 (0) 1280 814169

Email [sales@milpower.co.uk](mailto:sales@milpower.co.uk)  
Web Page. [www.milpower.co.uk](http://www.milpower.co.uk)