MIL/BB-LA6 Battery

- NATO cage code: KE507
- High performance rechargeable sealed lead acid battery.
- Durable high impact plastic housing and connector enclosure
- High reliability due to all welded construction
- Contains internal PTC protection
- 100% final testing

This battery is engineered and designed for use in a world wide tactical environment, and is manufactured to meet and exceed US MIL-SPEC and ISO9000 methods and procedures. This battery meets the requirements of MIL-B-11188 with reference to MIL-STD-810 for:

Battery voltage	Capacity test	Electrolyte leakage
Mechanical and thermal shock	Vibration	Insulation resistance

For use in	AN/PRC-77 and AN/PRC-1077,AN/PRC-1099 radio sets
Replacement for	BB-586/U, BB-386/U, BA-386/U, BA-5598/U, TNC386, & TNC386/H
Cell chemistry	Sealed lead acid (lead calcium)
Nominal voltage	12 Volts
Typical capacity	5.2Ah
Protection	Internal re-settable fuse (PTC)
Nominal dimensions	240 x 92 x 54mm
Nominal weight	2.25kg
Connector	Floating type, 2 phosphor bronze pins fitted
Case material	Modified ABS
Operating temperature	-20°C to +55°C
Storage temperature	-40°C to +55°C

MIL Power Limited.
Celtic House, 44 Ball Moor,
Buckingham. MK18 1RQ
England

MIL Power

Tel No. +44 (0) 1280 812402
Fax No. +44 (0) 1280 814169

Email sales@milpower.co.uk
Web Page. www.milpower.co.uk