MIL/MC3005 Military Battery Charger for BB-586/U



- 2 way charger for military BB-586/U batteries. Also available as 3, 4 or 5 output.
- 115/230V ac, or 24V dc supply for vehicle use
- Robust construction and easy grip handles for portability
- Vehicle mounting kit includes mounting plate and dc power lead

Charger functions include:

- Pre charge test to check battery fit to charge
- Normal charge 14 hour timed charge
- Balance charge trickle charge to maintain capacity at completion of normal charge.

The MIL/MC3005 is designed and manufactured in the UK giving the user unbeatable product support.

Dimensions	290mm x 190mm x 160mm
Weight	5kg
Normal charge current	400mA
Balance charge current	200mA
Charge termination	Timed
Number of channels	2
Output	Flying lead
Output power	20 Watts
Supply voltage	110V/230V ac internally switched 50/60Hz, 20V-30V dc
Charging temperature	0°C to +50°C
Storage temperature	-20°C to +70°C

MIL Power Limited. Celtic House, 44 Ball Moor, Buckingham. MK18 1RQ England

MIL Power

 Tel No. +44 (0) 1280 812402
 Email
 sales@milpower.co.uk

 Fax No. +44 (0) 1280 814169
 Web Page. www.milpower.co.uk