

MIL POWER LTD

Delivering Battery Performance

MIL/LP8-10-1M, 14.8V 10Ah Lithium Polymer Battery with LED Gas-Gauge for Inova Firefly & Hawk Seismic Recorders

- High performance rechargeable Lithium polymer batteries with LED gas-gauge.
- Available as small case 14.8V 10Ah.
- Also available as standard case 14.8V 20Ah.
- High capacity performance verified cells.
- Robust user replaceable output cable with an industry standard connector.
- Sealed waterproof high impact plastic enclosure.
- Protection against short circuit and overload.
- Protection against over discharge and over charge.
- Cell balancing for increased cycle life.
- Integral security loop.
- Connector for Firefly & Hawk Seismic Recorders.

Applications for our batteries include:

- Seismic exploration.
- Telemetry.
- Precision sensors.
- Recording instrumentation and equipment.
- Seismology.
- Geophysical and geotechnical hardware.





MIL POWER LTD

Delivering Battery Performance

MIL/LP8-10-1M, 14.8V 10Ah Lithium Polymer Battery with LED Gas-Gauge for Inova Firefly & Hawk Seismic Recorders

- Small case, only 6.93" x 3.35" x 2.52".
- Ultra lightweight 3lbs.
- High performance rechargeable Lithium polymer batteries.
- High capacity performance verified cells.
- Sealed waterproof high impact plastic enclosure.
- Protection against short circuit and overload.
- Protection against over discharge and over charge.
- Cell balancing for increased cycle life.

Cell chemistry	Lithium polymer
Nominal Voltage	14.8 Volts
Maximum Voltage	16.8 Volts, open circuit
End of discharge Voltage	11 Volts
Typical capacity @ +25°C/+77°F	10.0 Amp hour at 2A discharge
Typical capacity @ -20°C/-4°F	9.6 Amp hour at 2A discharge
Typical capacity @ +60°C/+140°F	9.4 Amp hour at 2A discharge
Typical capacity @ -40°C/-40°F	8.0 Amp hour at 200mA discharge
Maximum discharge current	3 Amps
Charge retention	>80% after 28 day storage at +21°C, +70°F
Electrical protection	Over charge, over discharge, short circuit and overload.
Secondary protection	PTC auto resettable fuse
Case dimensions excluding connector	176 x 85 x 64 mm, 6.93" x 3.35" x 2.52"
Nominal weight	1.35 kg, 3lbs
Case material	Yellow high impact resistant plastic which meets UL94 V-0
Operating temperature, charging	0°C to +40°C, +32°F to +104°F
Operating temperature, discharging	-40°C to +60°C, -40°F to +140°F
Storage temperature, 1 month	-20°C to +45°C, -4°F to +113°F
Storage temperature, 3 months	0°C to +30°C, +32°F to +86°F
Storage temperature, long term	+15°C to +25°C, +59°F to +77°F